

Cut Sheet - 303030 Outdoor Cabinet w/Minipack 4.8kW

Preconfigured Cabinet System Model: 303030 w/T29 Air Conditioner – SOLD AS IS



EV Part Number: 261996

Product configuration details:

Base Cabinet

- 303030 Cabinet (30"Wx30"Dx61.25"H, 30RU)
- UL Type 3 Listed Enclosure, GR487 capable
- 3 point latching system with Bellcore Electronics (7/16th) handle and pad lock hasp
- Integrated Solar Shield
- Front & Rear rails w/23"-19" Adapters, 20U (Incl. Power)
- Dual adjustable thermostat for cabinet temp alarms
- Interior LED light with on/off switch
- Front and Rear door alarm with technician override
- 10 Position Ground Bar with external cabinet Gnd studs

Cooling

- 4000BTU Air Conditioner w/1000W heater
- At 45°C Outdoor Temp, Capable of:
3500BTU [1025W] Heat Load; Internal Temp: 40°C
4000BTU [1170W] Heat Load; Internal Temp: 50°C

AC Power

- 220-240VAC input to externally mounted AC Load Center
- 100A Main Breaker w/breakers for other AC Components
- Outlet, Quad GFCI, 20A, 110VAC
- AC Smoke Detector with Alarm Output

See installation manual for more details:

Contact your Sales Representative for additional information.

(Cont)

- Generator Connector, 100A Appleton, w/Manual Interlock and 100A Breaker
- AC Surge Suppressor, 60kA, wired to Main AC Lugs
- AC Fail Relay Contact with Alarm Output wired to Main AC Lugs

Cable Entry

- Bottom Ports available for Entry Through Concrete Pad
- 2x 4" SitePro Boots on Side Access Panel (No Inserts)

Battery Tray

- 1 Battery Tray w/cables (8RU) capable of holding up to (4) 190Ahr batteries max (comes with 100Ahr seismic straps)

Alarming

- I/O Monitor for cabinet and customer alarming, CAN connection to Smartpack Controller

DC Power

- Minipack 4.8kW, -48VDC, 100A system, 6 Slots, 2RU
- Qty (4) 800W Minipack Rectifiers
- Qty (4) 5A & Qty (4) 15A DC Load Breakers
- Battery temp sensor
- Includes Smartpack WEB/SNMP Controller
- 14 position ground bar for Polyphaser, Coax, DC surge suppression